



SMYLE



- Ideal for villa applications
- Only 99 mm wide, ideal for mounting on poles
- Two-size name tags and buttons: 15 x 60 and 30 x 60 mm
- Can be flush-mounted using the 1128/50 kit
- IP 44

Small, fun design for one and two-family villas. Smyle is ideal for villa applications and villa compounds as secondary entry panel in combination with Genya (positioned at main entrance). Available in door phone and video door phone versions (with semi pin-hole camera, adjustable by hand), Smyle has a smooth style minimum width to be installed on gate poles.

SMYLE AND SYSTEM COMPATIBILITY TABLE

Coax

4+n



SMYLE mod. 1129 - 1729



1129/1



1129/2




1729/1



1729/2



1729/6



1728/80

SMYLE ENTRY PANEL

Code	Description	System	Notes
1129/1	One-family audio entry panel	Audio 4+n Video Coax	Green LED backlighting. Wall-mounted installation.
1129/6	One-family audio entry panel in metal version (Zama)	Audio 4+n Video Coax	Green LED backlighting. Wall-mounted installation.
1129/2	Two-family audio entry panel	Audio 4+n Video Coax	Green LED backlighting. Wall-mounted installation.
1729/1	One-family video entry panel	Audio 4+n Video coax Video 5 wires	Green LED backlighting. Wall-mounted installation.
1729/2	Two-family video entry panel	Audio 4+n Video Coax Video 5 wires	Green LED backlighting. Wall-mounted installation.
1729/6	Low-profile wall mounted one-family entry panel with shockproof front	Audio 4+n Video coax Video 5 wires	Green LED backlighting. Wall-mounted installation.

Dimensions (W x H x D) 99 x 180 x 35 mm

Name tag dimensions (W x H): 60 x 15 mm for 1729/2 and 1129/2

Name tag dimensions (W x H): 60 x 35 mm for 1729/1 and 1129/1

ACCESSORIES

1129/50	Flush-mounting box with aluminium rim and frame Suitable for installing semi-flushed Smyle audio/video entry panel. Frame dimensions: W 131 x H 218 mm Dimensions of flush-mounting box: W 115 x H 209 x D 47 mm
1129/60	As 1129/50 but in ZAMA

LOUDSPEAKING UNITS/CAMERAS

Code	Description	Camera	System	Notes
1728/40**	Camera module with loudspeaking unit		Coax	
1728/80**	Camera module with loudspeaking unit	B/W	Coax	
956/123	Camera module with loudspeaking unit	B/W	5 wires	For use in Smyle entry panel for managing a second door in 956/41-42 kits.
956/129	Camera module with loudspeaking unit, 60 Hz.	B/W	5 wires	For use in Smyle entry panel for managing a second door in 956/41-42 kits.
1128/500	Loudspeaking unit	-	Audio 4+n	Provided with mechanical adapter for use in Exigo 725-625 entry panels. Replaces 5150/500.
1128/510	Loudspeaking unit	-	Audio 4+n	Provided with mechanical adapter for use in Exigo 725-625 entry panels. Replaces 5150/510. 12Vac power.

See price list for spare parts. Colour. ** Contact the sales network for availability.